

MACHINE VISION

Systems - Sensors - Software



Tens of thousands of applications worldwide inspect billions of products each day, many products that simply could not be manufactured without machine vision technology. Whether verifying the fill levels of soda bottles traveling on a conveyor, reading oil-stained codes on automotive parts or positioning touch screens on smartphones to micron-level accuracy, machine vision technology performs highly-detailed tasks on high-speed production lines.

Cognex's comprehensive line of sensors and 2D and 3D systems all use machine vision technology to perform inspections but are engineered for different tasks.







	Vision Sensors	2D Vision	3D Vision
Presence/Absence	✓	✓	✓
Q Defect Detection	✓	✓	✓
Assembly Verification	✓	✓	✓
Gauge/Measure	\checkmark	✓	√
Q Cosmetic Inspection		√	√
Guide/Align		✓	✓
03/04 OCR/OCV	✓	✓	
Code Reading		✓	

INDUSTRY-LEADING VISION TECHNOLOGY

Cognex machine vision provides the power and flexibility to solve your most challenging manufacturing applications. Whether for inspection or robotic guidance, you can choose from a robust library of Al- or rule-based technologies that include classification, defect detection, feature location, optical character recognition (OCR), measurement, and more capabilities.

Cognex Al

Cognex Al learns to spot patterns and anomalies from example images. It solves tasks that are too complicated and time-consuming to program with rule-based algorithms, while providing a consistency and speed that aren't possible with manual inspection.




Edge learning: Deploy in minutes

Edge learning is a subset of AI in which processing takes place on-device, or "at the edge," using a pretrained set of algorithms. The technology is simple

to setup, requiring smaller image sets and shorter training and validation periods than traditional deep learning-based solutions.









Deep learning: Analyze fine details

Capable of processing large, detailed image sets, deep learning is designed to automate complex or highly customized applications. The technology

enables users to analyze vast image sets quickly and efficiently, while differentiating between acceptable and unacceptable anomalies, to deliver accurate results.





Rule-based technologies


Cognex rule-based algorithms solve diverse applications from guiding assembly to automating inspections to expediting production and distribution. Designed for specialized tasks with consistency and low variation, these patented technologies are used in virtually all industry sectors to expedite and improve manufacturing.




Object locationFind geometric patterns on parts under inspection




Bead inspection Run high-precision inspections on beads and edges




Edge inspection
Locate edges, features, and
measure width



Histogram and image processing Measure thresholds and prepare images for analysis



Measurement toolsEstablish reliable featurebased parameters and thresholds



Color tools
Run color-based analysis for a range of applications




IdentificationEnsure high read rates for 1D and 2D barcodes



Optical character
recognition
Automate character reading
and decipher text

Advanced imaging technologies



HDR+
Delivers high-contrast images for multi-point inspections of parts with varying depths of field and lighting conditions.





SurfaceFX
Isolates features and
defects that are recessed or
embossed on parts such as
chips, wrinkles, punctures,
stamped text, and codes.



Cognex In-Sight 2D vision systems are unmatched in their ability to inspect, identify, and align parts. These self-contained, industrial-grade vision systems combine a library of advanced vision tools with high-speed image acquisition and processing. A wide range of models, including line scan and color systems, meet most price and performance requirements.

In-Sight 3800 Series

Designed for high-speed applications, In-Sight 3800 delivers a fully integrated solution for manufacturing automation. Beyond speed, this powerful system is embedded with the latest vision technologies and offers high flexibility and high resolution, allowing users to maximize throughput, scale their solution, and run more accurate inspections.







RESOLUTION



FEATURES


























In-Sight 2800 Series

The In-Sight 2800 vision system combines edge learning technology with traditional rule-based vision to solve a range of error-proofing tasks. From presence/absence detection to sortation and character reading applications, this fully integrated vision system offers an easy-to-use solution for automating inspections.







RESOLUTION





















In-Sight D900 Series

The In-Sight D900 vision system leverages advanced Al-based tools to solve challenging OCR, assembly verification, and defect detection tasks. Processing takes place on-device, which eliminates the need for a PC, simplifying application deployment.













RESOLUTION


























In-Sight 9000 Series

Rugged, ultra-high-resolution standalone vision system solves high-accuracy part location, measurement, and inspection applications. Line scan and area scan image acquisition options are available for imaging large, continuously moving or stationary objects.





In-Sight 8000 Series

Ultra-compact standalone vision system delivers industry-leading performance in



In-Sight 7000 Series

Combines modular integrated lighting with powerful vision tools in a compact footprint to deliver fast, accurate inspections on space-constrained production lines.





VISION SENSORS

Vision sensors perform simple pass/fail applications that help ensure products manufactured on an automated production line are error-free and meet specified quality standards. Cognex vision sensors provide reliable inspections thanks to powerful vision tools, integrated lighting, and hardware modularity.

In-Sight 2000 Series

Ideal for solving common error-proofing applications, these vision sensors offer high value and ease of use and the flexibility to adapt to virtually any production line environment.

In-Sight 2000 Mini

All the power of the In-Sight 2000 vision sensor in an ultra-compact form factor allows users to deploy vision sensors in machines or production lines with limited mounting space.

TOOL SET

RESOLUTION



Up to 1.2MP

























POWERFUL AND FLEXIBLE IMAGING TECHNOLOGY

Modular, scalable architecture for current and future needs

When it comes to factory automation, one size rarely fits all. That's why many In-Sight products provide users with the flexibility to customize the system for their specific application and easily adjust as needs change.



Get better inspection results with the right imaging accessories

Multi-colored **LED lights** minimize the need for expensive external lighting and enhance specific features or text.

Polarizers reduce glare or hot spots and enhance contrast so objects can be recognized.

Color filters create contrast to lighten or darken features of the object.



Ambient light



Monochrome with blue light



No filter



With linear polarizer



Original color




or No filter




Blue Bandpass Filter

2D VISION APPLICATIONS

Automotive









Electronics







Food & Beverage













Pharmaceutical and Medical











2D VISION SPECIFICATIONS

	2000 Series	2800 Series	3800 Series	7000 Series	8000 Series	9000 Series	D900 Series
■ Image							
Imager Type	Monochrome/ Color Area Scan	Monochrome/ Color Area Scan	Monochrome/ Color Area Scan	Monochrome/ Color Area Scan	Monochrome/ Color Area Scan	Monochrome/ Color Area Scan, Monochrome line scan	Monochrome/ Color Area Scan
Resolution	Up to 1.2MP (1280 x 960)	Up to 1.6 MP (1440 x 1080)	Up to 5MP (2448 x 2048)	Up to 5MP (2448 x 2048)	Up to 5MP (2448 x 2048)	12MP (4096 x 3000), 32MP (2048 x up to 16,384 lines) for line scan	Up to 5MP (2592 x 1944)
Acquisition Speed (Max)	75 fps	Up to 45Hz	Up to 200 fps	Up to 217 fps	Up to 217 fps	Up to 14 fps, 66K lines per second for line scan	Up to 51 fps
Options 0							
Lenses	S-Mount, Autofocus	S-Mount, Autofocus	C-Mount, Autofocus	C-Mount, S-Mount, Autofocus	C-Mount	C-Mount	C-Mount, S-Mount, Autofocus
Lighting	Integrated	Integrated	Integrated, External light via light control connector	Integrated, External light via light control connector	N/A	External light via light control connector (area scan only)	Integrated, External lights via light control connector
Networking	ng						
Speed			Gigabit	Ethernet (10/100/100	0 Mbps)		
General Protocols	TCP/IP, UDP, FTP, Telnet, RS-232C	TCP/IP, FTP	TCP/IP, FTP	TCP/IP, I	JDP, FTP, SFTP, Telno	et, SMTP	TCP/IP, FTP
Industrial Protocols	OPC UA, EtherNet/IP with AOP, PROFINET Class B, iQSS, Modbus TCP, SLMP/SLMP Scanner, CC-Link IE Field Basic	PROFINET, EtherNet/IP, SLMP, OPC/UA	PROFINET, EtherNet/IP, SLMP, OPC/UA	OPC UA, EtherNet/IP with AOP, PROFINET Class B, iQSS, Modbus TCP, SLMP/SLMP Scanner, CC-Link IE Field Basic, IEEE 1588 (CIP Sync)	OPC UA, EtherNet/IP with AOP, PROFINET Class B, iQSS, Modbus TCP, SLMP/SLMP Scanner, CC-Link IE Field Basic	OPC UA, EtherNet/IP with AOP, PROFINET Class B, iQSS, Modbus TCP, SLMP/SLMP Scanner, CC-Link IE Field Basic, IEEE 1588 (CIP Sync)	Ethernet/IP with AOP, Profinet Class A, Profinet Class B
2 I/O							
Trigger input	1	1	1	1	1	1	1
General purpose input	1	1	1	1		1	1
General purpose output	4	2	2	2	2	2	2
Bi-Directional		2	2	2		2 (area scan only)	2
Encoder						2 (line scan only)	
Expansion I/O	CIO-1400			CIO-1400, CIO-Micro	CIO-Micro	CIO-1400, CIO-Micro	
Serial	RS-232C			RS-232C	RS-232C	RS-232C	

	2000 Series	2800 Series	3800 Series	7000 Series	8000 Series	9000 Series	D900 Series
Mechanic	cal						
Length	In-line: 92 mm (3.61 in), Right-angle: 61 mm (2.42 in)	In-line: Up to 110 mm (4.3 in), Right- angle: Up to 68 mm (2.7 in)	Up to 117 mm (4.6 in)	90.1 mm (3.54 in)	75.5 mm (2.97 in)	121.0 mm (4.77 in)	121.0 mm (4.77 in)
Width	60 mm (2.38 in)	Up to 69 mm (2.7 in)	Up to 104 mm (4.1 in)	60.5 mm (2.38 in)	35 mm (1.38 in)	60.5 mm (2.38 in)	60.5 mm (2.38 in)
Depth	52 mm (2.05 in)	Up to 104 mm (4.1 in)	Up to 181 mm (7.1 in)	Up to 2MP: 35.7 mm (1.41 in), 5MP: 49.4 mm (1.94 in)	32 mm (1.26 in)	53.4 mm (2.10 in)	53.4 mm (2.10 in)
Protection	IP65	IP67	IP67	IP67	IP40	IP67	IP67
S Vision Too	ols						
Cognex Al		✓	✓				√
Pattern Matching	√	✓	✓		✓ Available PatMax	x and PatMax RedLine	.
Blob	√		✓	✓	✓	✓	√
Edge	√	✓	✓	✓	✓	✓	√
Measurement	√	✓	✓	✓	✓	✓	√
1D/2D Code Reading		✓ IDMax®, PowerGrid®, Hotbars®	✓ IDMax, PowerGrid, Hotbars	✓ IDMax, PowerGrid, Hotbars	✓ IDMax, PowerGrid, Hotbars	✓ IDMax, PowerGrid, Hotbars	✓ IDMax
OCR	✓	✓	✓	✓	✓	✓	✓
Flaw Detection				✓	✓	✓	✓
Color Verification	✓			✓	✓	✓	√
Color Identification				✓	✓	✓	√
Histogram		✓	✓	✓	✓	✓	√
Brightness	✓	✓	✓	✓	✓	✓	√
Pixel Counting	√	✓	✓	✓	✓	✓	√
Contrast	√	✓	✓	✓	✓	✓	√
Image Filters	✓	✓	✓	✓	✓	✓	✓



Whether performing a single profile measurement or scanning an entire surface, Cognex has the most powerful and robust 3D vision tools. Manufacturers in all industries trust Cognex technology to deliver high accuracy surface measurements that go beyond the capabilities of 2D vision technology.

In-Sight 3D-L4000 Series

A unique vision system combining 3D laser displacement technology with a high-performance smart camera. It allows factory engineers to quickly, accurately, and cost effectively solve a wide variety of inspections thanks to a comprehensive suite of true 3D vision tools, easy setup, and speckle-free blue laser optics.

TOOL SET 3D RESOLUTION





















3D-A5000 Series

State-of-the-art area scan camera captures high-resolution 3D point cloud images in less time than alternative methods. Using unique 3D imaging technology, it solves challenging assembly verification, in-line metrology, and robotic guidance applications.



TOOL SET

3D RESOLUTION


















3D-L4000 with VisionPro

Powerful laser displacement sensor with PC-based development environment performs fast, accurate 3D inspections, measurements, and OCR character reading. Equipped with industry-leading 3D vision tools and delivers results in real-world units.

TOOL SET

3D RESOLUTION





FEATURES














3D VISION APPLICATIONS


Automotive









Consumer Packaged Goods










Electronics








Food & Beverage







3D VISION SYSTEMS SPECIFICATIONS

In-Sight 3D-L4000 Series

	IS3D-L4050	IS3D-L4100	IS3D-L4300		
3D Technology	Displacement Sensor				
Clearance Distance (CD)	92.00 mm (3.6 in) 130.00 mm (5.1 in) 180.00 mm (7.1				
Measurement Range (MR)	106.00 mm (4.2 in)	235.00 mm (9.3 in)	745.00 mm (29.3 in)		
Near FOV	55.00 mm (2.2 in)	75.00 mm (3.0 in)	95.00 mm (3.7 in)		
Far FOV	90.00 mm (3.5 in)	90.00 mm (3.5 in) 180.00 mm (7.1 in)			
Resolution X	28.6–46.9 µm 39.1–93.8 µm		49.5–239.6 µm		
Resolution Z	2.5–6.9 µm 4.4–25.9 µm 6.9–147.5 µm				
Acquisition Rate	Up to 4 kHz (after windowing down the sensor) (¹Up to 6 kHz)				
Protection	IP65				
Software	In-Sight Vision Suite				

3D-A5000 Series

	3D-A5120	3D-A5060	3D-A5030	3D-A5005		
3D Technology	3D LightBurst Technology™ Area Scan					
Clearance Distance (CD)	1000.0 mm (39.4 in) 1400.0 mm (55.1 in) 1465.0 mm (57.7 in) 299.3 m					
Measurement Range (MR)	1000.0 mm (39.4 in)	400.0 mm (15.7 in)	80.0 mm (3.1 in)	12.0 mm (0.5 in)		
Near FOV	900 x 675 mm (35.4 x 26.6 in)	520 x 390 mm (20.1 x 15.4 in)	280 x 210 mm (11.0 x 8.3 in)	60 x 44 mm (2.4 x 1.7 in)		
Far FOV	1760 x 1320 mm (69.3 x 52 in)	645 x 490 mm (25.4 x 19.3 in)	285 x 216 mm (11.2 x 8.5 in)	65 x 46 mm (2.6 x 1.8 in)		
Resolution X	626–1223 µm	361–454 μm	195–200 μm	42–44 μm		
Resolution Z	414–1656 µm 338–690 µm		178–213 μm	7–8 μm		
Acquisition Time	200 msec					
Protection	IP65					
Software	VisionPro & Cognex Designer					

3D-L4000 with VisionPro

	VP 3D-L4033	VP 3D-L4050	VP 3D-L4100	VP 3D-L4300		
3D Technology	Displacement Sensor					
Clearance Distance (CD)	93.00 mm (3.7 in)	00 mm (3.7 in) 92.00 mm (3.6 in) 130.00 mm (5.1 in) 180.				
Measurement Range (MR)	44.00 mm (1.7 in)	106.00 mm (4.2 in)	235.00 mm (9.3 in)	745.00 mm (29.3 in)		
Near FOV	33.00 mm (1.3 in)	55.00 mm (2.2 in)	75.00 mm (3.0 in)	95.00 mm (3.7 in)		
Far FOV	39.00 mm (1.5 in)	90.00 mm (3.5 in)	180.00 mm (7.1 in)	460.00 mm (18.1 in)		
Resolution X	17.2–20.3 µm	28.6–46.9 µm	39.1–93.8 µm	49.5–239.6 μm		
Resolution Z	1.7–2.7 µm 2.5–6.9 µm 4.4–25.9 µm 6.9–147.5					
Acquisition Rate	Up to 4 kHz (after windowing down the sensor) (¹Up to 6 kHz)					
Protection	IP65					
Software	VisionPro & Cognex Designer™					

¹ When binning is enabled and the FOV is windowed down.

VISION SOFTWARE

Cognex vision software provides the power and flexibility to solve your most challenging applications. Available in several formats, choose between programmatic or graphical user interfaces to meet your development needs and gain access to the industry's most robust vision tool libraries.

In-Sight Vision Suite

In-Sight Vision Suite software is common across all In-Sight products and offers flexible development options. It includes two programming environments — EasyBuilder® and spreadsheet - designed for different types of tasks, which allows you to seamlessly scale your solution as your application needs change.

EasyBuilder

With its point-and-click programming, the EasyBuilder interface is ideal for setting up simple or common jobs. The intuitive process guides developers step-by-step through setup — from image capture to the final result.

Spreadsheet

The spreadsheet interface is ideal for building advanced or customized applications. Robust in design, this development environment provides users with the ability to make critical adjustments to job parameters, without the need for programming.



Runtime visualization for real-time device management

Cognex offers a web-based, human-machine interface (HMI) and display panel for monitoring and controlling In-Sight vision systems, directly on the factory floor. From the HMI, users can view inspection results, configure applications, and modify setup parameters.



VisionPro

VisionPro® 10 is a PC-based software that combines best-in-class vision technologies in a graphical programming environment. Powerful enough to solve the most challenging vision tasks, it enables rapid deployment of highly-customizable applications, from geometric object location and inspection to identification, measurement, and alignment. With a future-oriented design that includes rule-based tools and AI capabilities, this flexible software supports both current and future vision needs.

TOOL SET










Extensive library of Al- and rule-based tools tackle your toughest vision challenges











THE GLOBAL LEADER IN MACHINE VISION AND BARCODE READING

For over 40 years, Cognex has helped the world's most innovative companies make their manufacturing and distribution faster, smarter, and more efficient.

Cognex vision systems and barcode readers help customers improve product quality and operational performance by eliminating defects, verifying assembly, and tracking information at every stage of the production process. Using data captured by Cognex vision systems and barcode readers, companies can monitor, update, and change production plans in real-time across global supply chains.

Smarter automation using Cognex products means fewer errors, which equates to lower costs and higher customer satisfaction. And Cognex is constantly applying new techniques, like artificial intelligence, to enable companies to evolve their automation strategy to meet today's and tomorrow's needs.

With a wide range of solutions and a large network of global vision experts, Cognex makes it possible to **Build Your Vision.™**

\$1 BILLION 2022 REVENUE

OVER 42
YEARS IN THE BUSINESS

500+ CHANNEL PARTNERS

GLOBAL OFFICES IN 20+ COUNTRIES

4,000,000+
SYSTEMS SHIPPED



BUILD YOUR VISION

Vision Systems

Automate inspection tasks, from defect detection to assembly verification and text reading, with easy to deploy vision systems.

www.cognex.com/machine-vision









Barcode Readers

Track and trace, from the floor to dock door, with powerful readers and verifiers designed to handle any code type.

www.cognex.com/barcodereaders









Industry Solutions

Solve applications across a wide range of industries with flexible and reliable machine vision and barcode reading solutions.

www.cognex.com/solutions









Companies around the world rely on Cognex vision and barcode reading solutions to optimize quality, drive down costs and control traceability.

Corporate Headquarters One Vision Drive Natick, MA 01760 USA

Regional Sales Offices

Americas

+1 844 999 2469 North America Brazil +55 11 4210 3919 +800 733 4116 Mexico

Europe

+43 800 28 16 32 Austria +32 289 370 75 Belgium Czechia +420 800 023 519 +33 1 76 54 93 18 +49 721 958 8052 Germany

Hungary Ireland Italy Netherlands Poland

Romania Spain Sweden Switzerland Turkey

United Kingdom

+36 800 80291 +353 21 421 7500 +39 02 3057 8196 +31 207 941 398

+44 121 29 65 163

+48 717 121 086 +40 741 041 272 +34 93 299 28 14 +46 21 14 55 88 +41 445 788 877 +90 216 900 1696 Asia-Pacific

Thailand

Vietnam

+61 2 7202 6910 Australia +86 21 2279 9455 +91 7305 040397 India Indonesia +62 21 80602011 Japan +81 3 5977 5400 Korea +82 2 539 9047 Malaysia +6019 916 5532 New Zealand +64 9 802 0555 Singapore +65 3158 3322 +886 02 7703 2848 Taiwan

+84 98 2405167

© Copyright 2023, Cognex Corporation. All information in this document is subject to change without notice. Cognex, PatMax RedLine, PatMax, In-Sight, VisionPro, EasyBuilder, IDMax, 2DMax, PowerGrid, and Hotbars are registered trademarks of Cognex Corporation. Build Your Vision, 1DMax, and SurfaceFX are trademarks of Cognex Corporation. All other trademarks are the property of their respective owners. Lit. No. VG9001-04-2023-EN

www.cognex.com